

Features

- ANDROSCAN = mini barcode scanner + Scan Holder
- ** With ANDROSCAN, it can make Android OTG smartphone become data collector. Plug and Play.
- ** Mini barcode scanner is with touch trigger. The operation is easy.
- ** Scan Holder can be used for different size of Android OTG devices. (from 4" to 6" size)
- ** ANDROSCAN has metal clip which can fix smartphone with ANDROSCAN easily.
- ** Scan holder solves the issue for micro USB port in the bottom of phone.
- ** Scan holder H92PH can provide power to mini barcode scanner.
- ** You don't need to remove Scan holder when in charge. You can charge the battery inside & smart-phone battery both through its micro USB port.
- ** Scan Holder has "Cable Storage Area" which stores redundant cable here.



Specifications :

Model Name	DC9252NPH		ZEBRA SE2707		DC9252NNH
Engine					
Performance Characteristics					
• Aiming LED	610 nm LED				
• Illumination Element	1 Hyper Red 660 nm LED				
• Depth of field	1D (20mil Code 39) : 420 mm max 2D (20mil QR Code) : 250 mm max				
• Sensor	CMOS (640×400 pixels)				
• Best resolution	1D (4mil) : Code 39 2D (6.6mil) : PDF417				
• Print contrast	≥ 20%				
• Reading angle	Tilt: 360° / Pitch ±60° / Skew ±60°				
• Charge	Micro USB port				
• Interface	USB HID, USB Serial <by request>				
• Cable supported	Micro USB cable or Type-C cable				
• Symbolologies	UPC-A, UPC-E, UPC-E1, EAN-8, EAN-13, ISBN, Code 128, UCC/EAN-128, ISBT 128, Code 39, Code39 Full ASCII, Trioptic Code 39, Code 32 (Italian Pharma Code), Code 93 , Code 11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Matrix 2 of 5, Codabar, MSI GS1 DataBar, PDF 417, MicroPDF417, Datamatrix, QR Code, Micro QR Code, Aztec, Composite, TLC-39, MaxiCode, Postal: US PostNet, US Planet UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX)				
• Scan Holder	with H92P (with battery) rechargeable Li-Ion 3.7V 900mAH		with H92N (without battery)		

Electrical Characteristics

• Input voltage	5 VDC ± 5%
• Current - operating	340 mA

Physical Characteristics

• Dimension (L x W x H)	125 x 52.5 x 32.5 mm
• Color of housing	Black
• Weight	134 g+/- 5 g 112g+/- 5 g

Environment

• Temperature-operation	0°C to 50°C
• Temperature-storage	-10°C to 60°C
• Humidity-operation	5% to 95% relative humidity, non-condensing

Decode Zone (DOF is measured at the office under 600 lux and by Standard barcode. There are +/- 10 mm Torrence. DOF may be also impacted by barcode quality and environmental conditions.)

• 4 mil Code 39	75 ~ 100 mm
• 5 mil Code 39	65 ~ 120 mm
• 13 mil UPC-A	60 ~ 300 mm
• 20 mil Code 39	100~ 420 mm
• 6.67 mil PDF417	75 ~ 110 mm
• 10 mil DataMatrix	70 ~ 140 mm
• 20 mil QR Code	55 ~ 250 mm

Product specification is subject to change without notice.