



ANDROSCAN for Android OTG device use

Features

ANDROSCAN = mini barcode scanner + Scan Holder

** With ANDROSCAN, it can make Android OTG smartphone become data collector.
Plug and Play.

** Mini barcode scanner is with touch trigger. The operation is easy.

** Scan Holder can be used for different size of Android OTG devices.
(from 4" to 6" size)

** ANDROSCAN has metal clip which can fix smartphone with ANDROSCAN easily.

** Scan holder solves the issue for micro USB port in the bottom of phone.

** Scan holder H92PH can provide power to mini barcode scanner.

** You don't need to remove Scan holder when in charge. You can charge
the battery inside & smart-phone battery both through its micro USB port.

** Scan Holder has "Cable Storage Area" which stores redundant cable here.



Specifications :

Model Name	DC9257APH	DC9257ANH
Engine	CCD ENGINE	
Performance Characteristics		
• Light source	610nm~640nm Red LED	
• Depth of field	13 mil EAN 13 : 440 mm max	
• Scan Rate	300 scans/sec	
• Best resolution	4 mil Code 39	
• Interface	USB Type-C or Micro USB (USB_HID ,USB Serial <by request>)	
• Print contrast	30% or more	
• Symbolologies	Code 128,EAN-13, EAN-8,, Code 39, UPC-A, UPC-E,Codabar,Interleaved 2 of 5, ISSN, ISBN,Code 93,MSI,Matrix 2 of 5,Industrial 2 of 5,Code 11,RSS-14 RSS-14-limited,RSS-14-expand	
• Scan Holder	with H92PH (with battery) rechargeable Li-Ion 3.7V 900mAH	with H92NH (without battery)
Electrical Characteristics		
• Input voltage	5 VDC ± 5%	
• Current - Reading	60 mA max	
Physical Characteristics		
• Dimension (L x W x H)	125 x 52.5 x 32.5 mm	
• Color of housing	Black	
• Weight	134 g+/- 5 g	112g+/- 5 g
Environment		
• Temperature-operation	0°C to 50°C	
• Temperature-storage	-10°C to 60°C	
• Humidity	Up to 95% relative humidity, non-condensing	
Depth of Field (DOF is measured at the office under 600 lux and by Standard barcode. There are +/- 10 mm Torrence. DOF may be also impacted by barcode quality and environmental conditions.)		
• 4 mil Code39	75mm ~ 180mm	
• 5 mil Code39	70mm ~ 200mm	
• 13 mil EAN 13	55mm ~ 440mm	

Product specification is subject to change without notice.

RIOTEC CO., LTD.

8F., 196-2, DaTong Rd., Sec. 3, Xizhi Dist., New Taipei City 221, Taiwan

TEL : +886-2-8647-1828

FAX : +886-2-8647-1800

E-mail : sales@riotec.com.tw

Web : www.riotec.com.tw