

## Mobile barcode scanner for Android OTG devices

## **Features**

- 2D Mini Mobile barcode scanners are designed for Android OTG devices especially.
- DC9267L: Wearing form design frees operator's hands to move packages, products or materials, helping to improve efficiency and productivity.
- Lightweight, ergonomically designed for easy operation
- 'With application, DC92xx series make Android OTG devices become data collector economically.



Specifications:	
Model Name	DC9267L
Engine	Al3200+ 2D ENGINE
<b>Performance Characterist</b>	tics
Light source	625±10 nm LED
<ul> <li>Depth of field</li> </ul>	1D (20 mil Code 39): 600 mm
Best resolution	1D (CODE39)≥ 4mil
	2D (PDF417) ≥ 6.67mil
Scan Angle	Tilt: 360° / Pitch ±50° / Skew ±50°
<ul> <li>Interface</li> </ul>	Micro USB ( USB_HID ,USB Serial by request> )
<ul> <li>Print contrast</li> </ul>	≧25%
• Symbologies	1D: Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, GS1 Databar, Codabar, Interleaved 2 of 5, ISBN/ISSN, Code 93, MSI, UCC/EAN-128, Matrix2 of 5, Industrial 2 of 5, Code 11,

2D: PDF417, Data Matrix ,QR Code, Micro QR code

Electrical Characteristics		
Input voltage	Smart Phone / Tablet Power	
<ul> <li>Current - operating</li> </ul>	220 mA	
<b>Physical Characteristics</b>		
• Dimension (L * W * H)	43 X 65 X 21 mm (without cable)	
<ul> <li>Color of housing</li> </ul>	Black	
<ul> <li>Weight</li> </ul>	42 g	
Environment		
<ul> <li>Temperature-operation</li> </ul>	0°C to 50°C	
<ul> <li>Temperature-storage</li> </ul>	-10°C to 60°C	
<ul> <li>Humidity-operation</li> </ul>	5% to 95% relative humidity, non-condensing	
Decode Zone (DOF is measured at the office under 600 lux and by Standard barcode. There are +/- 10 mm Torrence. DOF may be also impacted by barcode quality and environmental conditions.)		
4 mil Code 39	50mm -140mm	
• 5 mil Code 39	50mm -160mm	
• 13 mil UPC-A	60mm -360mm	
• 20 mil Code 39	100mm -600mm	
• 6.67 mil PDF417	60mm -160mm	
<ul> <li>10 mil DataMatrix</li> </ul>	50mm -120mm	
• 20 mil QR Code	30mm -280mm	

Product specification is subject to change without notice.

8F., 196-2, DaTong Rd., Sec. 3, Xizhi Dist., New Taipei City 221, Taiwan RIOTEC CO., LTD.

> FAX: +886-2-8647-1800 TEL: +886-2-8647-1828 Web: www.riotec.com.tw E-mail: sales@riotec.com.tw